



## D5T Dump Series

|   |   |
|---|---|
| • G.V.W.R.-9,950 #                        | • Axles - 2-5,200 # cambered brake axles          |
| • G.A.W.R.(Each Axle) - 5,200 #           | • Suspension - Double eye spring with equalizer   |
| • Coupler - 2 - 5/16" Adjustable          | • Tires - ST225/75/15" load range D               |
| • Safety Chain - 3/8" grade 43 with hooks | • Wheel -15" 6 bolt white spoke                   |
| • Jack -7,000 # drop leg                  | • Deck - 12 ga. smooth steel                      |
| • Frame - all tubing construction         | • Lights - D.O.T. stop, tail, turn, and clearance |
| • Tongue - 6" channel wrap around         | • Elec. Plug - 7-way RV                           |
| • 12 volt self contained pump             | • Paint - High solids acrylic enamel              |
|   | • Stake pockets on sides                          |
|   | • Sides-14 ga. smooth steel                       |

### Standard Features

### Optional Features

|                          |                                 |
|--------------------------|---------------------------------|
| • 15" white spoke wheels | • Higher sides                  |
| • Light protectors       | • Spare tire mount              |
| • Electric breakaway     | • 2-way side and top hinge gate |
| • E-Z Lube axles         | • Double barn doors             |
| • Charge post            | • Tarp System                   |
|                          | • Charger                       |

### Dimensions

| Length | A    | B   | C   | D     | E   |
|--------|------|-----|-----|-------|-----|
| 10'    | 120" | 79" | 42" | 33.5" | 76" |
| 12'    | 144" | 91" | 42" | 33.5" | 76" |

