



Commercial Series Gooseneck 10 TC Series Pierced Frame

• G.V.W.R. - 22,500 #	• Axles - 2 Dexter 10,000 # dual wheel electric brake axles
• G.A.W.R.(Each Axle) -10,000#	• Suspension - Multi-leaf slipper spring
• Coupler -adjustable gooseneck	• Tires - ST235/80R/16" load range D
• Safety Chain -3/8" grade 43 withhooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jack-10,000 # drop leg	• Deck - 2" pressure treated pine
• Frame -12" @ 19# I-beam	• Lights - D.O.T. stop, tail, turn, and clearance
• Crossmembers - 4" channel on 16" center	• Elec. Plug - 7-way RV
• Side rails - 8" channel with (10) D rings	• Paint - high solids acrylic enamel

Standard Features

Optional Features

• 16" dual wheels	• Boxend tail
• Crossmembers on 16" centers	• Spring loaded ramps
• Sealed modular wiring harness	• 12 ton capacity
• Electric breakaway	• Electric over hydraulic
• Oil bath axle	• Wood covered ramps
• 5' dovetail	• Headache rack
• 5' ramps spring loaded	• Electric over hydraulic disc brakes
• Locking tool box	
• Rubber mounted lights	
• Spare tire rack	

Dimensions

Length	A	B	C	D	E	Dove
25'	297"	190"	91"	34"	102"	60"
29'	345"	214"	91"	34"	102"	60"
31'	372"	226"	91"	34"	102"	60"
33'	393"	250"	91"	34"	102"	60"
35'	420"	262"	91"	34"	102"	60"
38'	456"	274"	91"	34"	102"	60"
40'	468"	286"	91"	34"	102"	60"

