



UTT Utility Series

| | |
|---|---|
| • G.V.W.R. - 7,000 # | • Axles - 2-3,500 # cambered brake axles |
| • G.A.W.R.(Each Axle) -3,500 # | • Suspension - Multi-leaf spring with equalizer |
| • Coupler - 2" | • Tire - 205-75-15" load range C |
| • Safety Chains 8/0 grade 30 with hooks | • Wheel - 15" 5 bolt white spoke |
| • Jack - top wind | • Deck - Pressure treated pine |
| • Frame - 2"x3"x3/16" | • Lights - D.O.T. stop, tail, and turn |
| • Crossmembers 3" x 2" x 3/16 angle | • Elec. Plug - 7-way RV |
| • Fenders - 9"x72" teardrop with backs | • Finish - High solids acrylic enamel |
| • Deck height 20" | |

Standard Features

Optional Features

| | |
|----------------------------|------------------------|
| • 15" white spoke rims | • 24" sides |
| • Pressure treated decking | • Expanded metal sides |
| • Light protector | • Swing up jacks |
| • Electric breakaway | • Wrap tongue |
| • E-Z Lube brake axles | |
| • 7 way RV plug | |

Dimensions

| Length | A | B | C | D | E |
|--------|------|-------|-------|-----|-----|
| 10' | 120" | 81.5" | 38.5" | 20" | 76" |
| 12' | 144" | 93" | 38.5" | 20" | 76" |
| 14' | 168" | 104" | 38.5" | 20" | 76" |
| 16' | 192" | 114" | 38.5" | 20" | 76" |
| 18' | 216" | 124" | 38.5" | 20" | 76" |
| 20' | 240" | 134" | 38.5" | 20" | 76" |

